

SPECIFICATION

1 PROJECTOR - PANASONIC VIDEO PROJECTOR D 12000 SXGA

- 3-chip high-performance DLP projector, HD resolution
- The geometric image adjustment for projection on curved surfaces
- DLP system, chip DMD 0,95" /diagonal/ x 3
- Resolution (1 400x 1 050) x 3 pixels
- The image ratio 4:3
- Performance 12 000 lumens, 4 lamp system
- 6000k lumen lamps x2
- Image Contrast Ratio 5 000:1
- Image size: 70" – 600" diagonally
- ACR - auto cleaning robot –automatic filter cleaning system
- Unique liquid cooling system
- Lens as an optional accessory
- Weight 35kg
- Inputs and outputs: (VIDEO IN, VIDEO OUT, S-VIDEO IN, RGB1/2, DVI-D IN, SERIAL IN, SERIAL OUT, REMOTE 1 IN, REMOTE 1 OUT, REMOTE 2 IN, LAN)
- Dynamical iris
- 10bit Colour Management
- Cinema Progressive-scan
- 3D colour management system
- Dynamic control of image sharpness
- Specially protected optical drive for harsh environments
- Optional long-life lamps
- Easy lamp and filter replacement
- Motorized horizontal and vertical lens shift
- Optional lenses to order
- Built-in functions:
 - Multi Screen processor /up to 10 x 10 units can be used for edge blending
 - Colour matching function
 - Network features / optional/: wired LAN system, web browser checking/monitoring, e-mail message alert
 - Multi Projector Monitoring & Control Software to control multiple projectors simultaneously

2 PROJECTION SCREEN - SCREENWORKS 40" OPEN AIR ELITEINFLATABLE SCREEN

- AIRSCREEN: inflatable PVC frame, the professional projection screen or banner are stretched on it. The strength and stability of the screen is guaranteed by a special low-noise ventilator (230V AC), which continuously keeps high pressure in the frame
- dimensions of the frame 14,5 x 10 metres
- dimensions of the screen 12 x 7 metres
- possible ratios: AIRSCREEN® Standard (2:1), Wide-screen – Cinemascope (2,39:1), Wide Screen (1,85:1), HDTV (16:9), TV (4:3)
- 50% stronger than regular screens
- easy connection to high voltage
- it has all the relevant fire safety accreditation
- all the layers and components are connected by high-frequency welding, to avoid potential structural breach caused by using traditional mechanical sewing.
- system of cables and stabilizing ropes provide excellent stability from 29 to 38 km/hod. (5 Beaufort)
- steel harpoons for anchoring to the ground
- 1 hour for assembling

3 MAGIC CINEMA SOUND PRO 4

- frequency range: 35Hz – 20kHz ± 3dB
- performance:
 - 2600 W / AES
 - 4200 W / PROGRAM
 - 5500 W / PEAK!!!!
- crossover: Active – LR 24dB/Octave
- sensibility: 108dB
- Max spl: 143,5 dB
- coverage: HOR. 90° ± 20° 160Hz – 19kHz
VER. 50° ± 30° 250Hz – 19kHz
- 1 SYSTEM: LF – 2 x 800 watt
MB – 2 x 450 watt
MF – 1 x 150 watt
HF – 2 x 25 watt
- dimensions according to layout: height (210 cm /160 cm), width (140 cm/200 cm), depth (90 cm/90 cm), weight (190 kg)